iSEMC

Rotary Floor Standing Digital Display DS-S55 Series

Rotary floor standing digital displays provide a visually stunning and versatile platform for communicating information and engaging audiences within indoor spaces. One of the key advantages of rotary floor standing digital displays is their ability to deliver clear and detailed visuals, their high-resolution visuals, flexibility in content management, and energy-efficient design make them an ideal choice for businesses and organizations seeking to captivate their viewers and deliver impactful messages in a visually appealing manner. such as shopping malls, airports, hotels, offices, and entertainment venues.



FEATURES

- Long life, high reliability
- High definition
- Full functioning
- Simply control
- Easy to maintenance
- Customized for the content showing
- Good heat dissipation
- Low power consumption
- Support 7*24 hours operation
- Support full HD 1920*1080P
- Free split screen
- It is ready to use when plugged in
- Different usage scenario



DS-S55 Series



SPECIFICATION

Product Name	Rotary Floor Standing Digital Display DS-S55
Panel Size	55"
Aspect Ratio	16:9
Display Area (mm)	1211.6 × 682
Best Resolution	1920 × 1080 / 3840×2160
Contrast Ratio	1200:1 / 4000:1 / 5000:1
Brightness (cd/m²)	500
Viewing Angle	178°
Response Time	6ms
Display Color	8 bit/16.7 Million
Lifespans	≥50000hour
Power Consumption	≤200W (standby ≤0.5W)
Voltage	100V-240VAC,50/60Hz
Speaker	10W/8 Ω ×2 Stereo Mixed Two-Channel CLASS-D Power Amplifier Output
Screen Material	4mm Tempered Explosion-Proof Glass
Touch	Optional
Power Supply	AC 100-240V.50-60HZ
Operating Temperature	0°C - 40°C
Operating Humidity	10% - 90% No Condensation
Storage Temperature	-20°C - 60°C
Storage Humidity	10% - 90% No Condensation
Installation Method	Floor-Standing Without Wheels





